AUTHOR INDEX

Anbukulandainathan, M., 235
Armenta, C., 189, 297
Armstrong, R. D., 15

Baker, S. V., 127
Balaramachandran, V., 235
Bartolozzi, M., 219
Barton, R. T., 287
Beaudoin, R., 177
Binder, L., 145

Chandrayan, V. R., 323, 331
Charles, E. A., 15
Cousseins, J. C., 81

Daoud, M., 81
de Andrés, M. C., 189
Doria, J., 189

Fullea, J., 189

Ganesan, M., 235
Geronov, Y., 35
González-Velasco, J., 273
Gopalakrishnan, K., 311
Graña, F., 189

Hamwi, A., 81
Harrison, J. A., 245
Haynes, A., 145
Hooper, A., 3
Hsien-Ming Wu, 59
Hsien-Wen Ko, 59
Hsiou-Jeng Shy, 59

Ilchev, N., 261
Izydorek, J., 337

Jindra, J., 91
Joshi, S. N., 167

Kapali, V., 235
Kordesch, K., 145
Kreuels, S., 201

Lakeman, J. B., 155
Lesinski, J., 337
Lim, H. S., 69

Manev, V., 35
Marshall, T. J., 3
Meiwes, J., 45
Micka, K., 91
Mitchell, P. J., 287
Moseley, P. T., 127
Moshtev, R. V., 35
Mrha, J., 91, 201
Muralidharan, V. S., 311
Murthy, A. S. N., 119
Musilová, M., 91

Neat, R. J., 3

Ovuru, S. E., 245

Paruthimal Kalaignan, G., 311
Pasquali, M., 29, 35
Pistoia, G., 29, 35
Powell, R. J., 3

Ramakrishnan, M., 311
Roberge, P. R., 177

Sarangapani, K. B., 235
Sathyanarayana, S., 167
Sharma, Y., 145
Sheik Mideen, A., 235
Singh, K., 323, 331
Skudelny, H.-Ch., 45
Smit, J., 177
Srivastava, T., 119
Stadnick, S. J., 69

Tejpal, A., 323
Turner, A. D., 127

Urrutia, J., 189

Vasu, K. I., 311
Venkatakrishna Iyer, S., 235
Verville, G., 177
Vielstich, W., 201
Vijayamohanan, K., 167
Vogel, U., 201

Werblan, L., 337

Yazami, R., 81

© Elsevier Sequoia/Printed in The Netherlands

AUTHOR INDEX

Anbukulandainathan, M., 235
Armenta, C., 189, 297
Armstrong, R. D., 15

Baker, S. V., 127
Balaramachandran, V., 235
Bartolozzi, M., 219
Barton, R. T., 287
Beaudoin, R., 177
Binder, L., 145

Chandrayan, V. R., 323, 331
Charles, E. A., 15
Cousseins, J. C., 81

Daoud, M., 81
de Andrés, M. C., 189
Doria, J., 189

Fullea, J., 189

Ganesan, M., 235
Geronov, Y., 35
González-Velasco, J., 273
Gopalakrishnan, K., 311
Graña, F., 189

Hamwi, A., 81
Harrison, J. A., 245
Haynes, A., 145
Hooper, A., 3
Hsien-Ming Wu, 59
Hsien-Wen Ko, 59
Hsiou-Jeng Shy, 59

Ilchev, N., 261
Izydorek, J., 337

Jindra, J., 91
Joshi, S. N., 167

Kapali, V., 235
Kordesch, K., 145
Kreuels, S., 201

Lakeman, J. B., 155
Lesinski, J., 337
Lim, H. S., 69

Manev, V., 35
Marshall, T. J., 3
Meiwes, J., 45
Micka, K., 91
Mitchell, P. J., 287
Moseley, P. T., 127
Moshtev, R. V., 35
Mrha, J., 91, 201
Muralidharan, V. S., 311
Murthy, A. S. N., 119
Musilová, M., 91

Neat, R. J., 3

Ovuru, S. E., 245

Paruthimal Kalaignan, G., 311
Pasquali, M., 29, 35
Pistoia, G., 29, 35
Powell, R. J., 3

Ramakrishnan, M., 311
Roberge, P. R., 177

Sarangapani, K. B., 235
Sathyanarayana, S., 167
Sharma, Y., 145
Sheik Mideen, A., 235
Singh, K., 323, 331
Skudelny, H.-Ch., 45
Smit, J., 177
Srivastava, T., 119
Stadnick, S. J., 69

Tejpal, A., 323
Turner, A. D., 127

Urrutia, J., 189

Vasu, K. I., 311
Venkatakrishna Iyer, S., 235
Verville, G., 177
Vielstich, W., 201
Vijayamohanan, K., 167
Vogel, U., 201

Werblan, L., 337

Yazami, R., 81

© Elsevier Sequoia/Printed in The Netherlands

SUBJECT INDEX

Accumulators
  current distribution in lead/acid and Ni/Cd, 45
a.c. impedance behaviour
  of Ni hydroxide and Ni/Co hydroxide electrodes in alkaline solution, 15
Active mass
  of lead/acid cell, role of additives in positive, 127
Additives
  role of, in positive active mass of lead/acid cell, 127
Alloys
  of commerical Al (2S) with Zn, In, Sn, and Bi as anodes for alkaline batteries, development of new, 235
Aluminium
  development of new alloys of commercial Al (2S) with Zn, In, Sn, and Bi as anodes for alkaline batteries, 235
Anode gel
  effect of amount of electrolyte in, on rechargeability of alkaline MnO_2–Zn cells, 145
Anodes
  for alkaline batteries, development of *new alloys of commercial Al (2S)* with Zn, In, Sn, and Bi as, 235

Batteries
  anodes for alkaline, development of new alloys of commercial Al (2S) with Zn, In, Sn, and Bi as, 235
  lead–acid
    determination of state-of-charge in, by means of reference cell, 297
    with electrolyte circulation, new method of establishing state of charge of, 189
    estimation of residual capacity of maintenance-free; identification of parameter for prediction of state-of-charge, 287
    oxygen cycle in sealed, 91
    Pb/Pb sulphate reference electrode for, new, 167
    positive plate reactions, effect of lignosulphate type additive on, 245
    voltage noise measurements on sealed, 177
  lithium
    application of chemical synthesized polypyrrole for rechargeable, 59
    improved cathode material for high rate rechargeable; small particle-size Li–V oxide, 35
    new graphite fluorides as electrode materials in, 81
    pulse discharge characteristics of solid-state, 3
    synthesis of FeS for, 337
Bibliography
  historical; development of Redox flow batteries, 219
Bismuth
  development of new alloys of commercial Al (2S) with Zn, In, Sn, and Bi as anodes for alkaline batteries, 235
  primary 1.5 V Li cells with $BiVO_4$ cathodes, 29

Cadmium
  current distribution in lead/acid and Ni/Cd accumulators, 45
Cathode material
  small particle-size Li–V oxide; improved, for high rate rechargeable Li batteries, 35
Cathodes
  $BiVO_4$, primary 1.5 V Li cells with, 29
Cell(s)
  galvanic, performance of $30Li_2SO_4$: $70Ag_2SO_4$ solid electrolyte in, 331
  lead/acid, role of additives in positive active mass of, 127
  lead–acid traction, real-time charge efficiency monitoring and on-charge gas evolution in tall, 155
  Li, primary 1.5 V, with $BiVO_4$ cathodes, 29
  Li–MnO_2, comparison of electrolytic and chemical MnO_2 in Li button cells at high discharge rates, 261
  MnO_2–Zn, effect of amount of electrolyte in anode gel on rechargeability of alkaline, 145

© Elsevier Sequoia/Printed in The Netherlands

N–H, storage capacity, effect of precharge on, 69
PbO_2/Pb, operation of oxygen cycle during charge and discharge of sealed, using separator as electrolyte carrier, 201
redox-flow, Fe(III)/Fe(II)–ligand systems for use as negative half-cells in, 119
Charge efficiency monitoring
real-time, and on-charge gas evolution in tall lead–acid traction cells, 155
Cobalt
a.c. impedance behaviour of Ni hydroxide and Ni/Co hydroxide electrodes in alkaline solution, 15
Current distribution
in lead/acid and Ni/Cd accumulators, 45

Electrical conductivity
of system of Ag_2SO_4:AgI eutectic added to $30Li_2SO_4$:$70Ag_2SO_4$, 323
Electrode(s)
Au, electro-oxidation mechanism of glyoxal on, in acidic media, 273
Ni hydroxide and Ni/Co hydroxide, in alkaline solution, aspects of a.c. impedance behaviour of, 15
Electrode materials
new graphite fluorides as, in Li batteries, 81
Electrolyte
effect of amount of, in anode gel on rechargeability of alkaline MnO_2–Zn cells, 145
lead–acid batteries with, circulation, new method of establishing state of charge of, 189
performance of $30Li_2SO_4$:$70Ag_2SO_4$ solid, in galvanic cells, 331
Electrolyte carrier
operation of oxygen cycle during charge and discharge of sealed PbO_2/Pb cell using separator as, 201
Electro-oxidation mechanism
of glyoxal on Au electrode in acidic media, 273

Galvanic cells
performance of $30Li_2SO_4$:$70Ag_2SO_4$ solid electrolyte in, 331
Gas evolution
real-time charge efficiency monitoring and on-charge, in tall lead–acid traction cells, 155
Glyoxal
electro-oxidation mechanism of, on Au electrode in acidic media, 273
Gold electrode
electro-oxidation mechanism of glyoxal on, in acidic media, 273
Graphite fluorides
as electrode materials in Li batteries, new, 81

Hydrogen
effect of precharge on Ni–H cell storage capacity, 69

Indium
development of new alloys of commercial Al (2S) with Zn, In, Sn, and Bi as anodes for alkaline batteries, 235
Iron
Fe(III)/Fe(II)–ligand systems for use as negative half-cells in redox-flow cells, 119
Ni–Fe cell, assessment of performance characteristics of, 311
synthesis of FeS for Li batteries, 337

Lead
PbO_2/Pb cell, operation of oxygen cycle during charge and discharge of sealed, using separator as electrolyte carrier, 201
Pb/Pb sulphate reference electrode for lead/acid battery research, new, 167
Lead/acid accumulators
current distribution in, 45
Lead–acid batteries
determination of state-of-charge in, by means of reference cell, 297
with electrolyte circulation, new method of establishing state of charge of, 189
estimation of residual capacity of maintenance-free; identification of parameter for prediction of state-of-charge, 287
oxygen cycle in sealed, 91
positive plate reactions, effect of lignosulphate type additive on, 245
voltage noise measurements on sealed, 177
Lead/acid battery research
new Pb/Pb sulphate reference electrode for, 167

Lead/acid cell
role of additives in positive active mass of, 127
Lead–acid traction cells
real-time charge efficiency monitoring and on-charge gas evolution in tall, 155
Ligand systems
Fe(III)/Fe(II)–, for use as negative half-cells in redox-flow cells, 119
Lignosulphate type additive
effect of, on lead–acid battery positive plate reactions, 245
Lithium
electrical conductivity of system of Ag_2SO_4:AgI eutectic added to $30Li_2SO_4$:$70Ag_2SO_4$, 323
performance of $30Li_2SO_4$:$70Ag_2SO_4$ solid electrolyte in galvanic cells, 331
small particle-size Li–V oxide; improved cathode material for high rate rechargeable Li batteries, 35
Lithium batteries
application of chemical synthesized polypyrrole for rechargeable, 59
improved cathode material for high rate rechargeable; small particle-size Li–V oxide, 35
new graphite fluorides as electrode materials in, 81
pulse discharge characteristics of solid-state, 3
synthesis of FeS for, 337
Lithium button cells
comparison of electrolytic and chemical MnO_2 in, at high discharge rates, 261
Lithium cells
primary 1.5 V, with $BiVO_4$ cathodes, 29

Manganese dioxide
comparison of electrolytic and chemical MnO_2 in Li button cells at high discharge rates, 261
–Zn cells, effect of amount of electrolyte in anode gel on rechargeability of alkaline, 145

Nickel
a.c. impedance behaviour of Ni hydroxide and Ni/Co hydroxide electrodes in alkaline solution, 15
current distribution in lead/acid and Ni/Cd accumulators, 45
effect of precharge on Ni–H cell storage capacity, 69
–Fe cell, assessment of performance characteristics of, 311

Oxygen cycle
operation of, during charge and discharge of sealed PbO_2/Pb cell using separator as electrolyte carrier, 201
in sealed lead–acid batteries, 91

Performance characteristics
of Ni–Fe cell, assessment of, 311
Polypyrrole
application of chemical synthesized, for rechargeable Li battery, 59
Positive active mass
of lead/acid cell, role of additives in, 127
Positive plate reactions
lead–acid battery, effect of lignosulphate type additive on, 245
Precharge
effect of, on Ni–H cell storage capacity, 69
Pulse discharge characteristics
of solid-state Li batteries, 3

Rechargeability
of alkaline MnO_2–Zn cells, effect of amount of electrolyte in anode gel on, 145
Redox flow batteries
development of; historical bibliography, 219
Redox-flow cells
Fe(III)/Fe(II)–ligand systems for use as negative half-cells in, 119
Reference electrode
new Pb/Pb sulphate, for lead/acid battery research, 167
Residual capacity
estimation of, of maintenance-free lead–acid batteries; identification of parameter for prediction of state-of-charge, 287

Silver
electrical conductivity of system of Ag_2SO_4:AgI eutectic added to $30Li_2SO_4$:$70Ag_2SO_4$, 323
performance of $30Li_2SO_4$:$70Ag_2SO_4$ solid electrolyte in galvanic cells, 331

State-of-charge
determination of, in lead–acid batteries by means of reference cell, 297
identification of parameter for prediction of; estimation of residual capacity of maintenance-free lead–acid batteries, 287
of lead–acid batteries with electrolyte circulation, new method of establishing, 189
Storage capacity
effect of precharge on Ni–H cell, 69

Tin
development of new alloys of commercial Al (2S) with Zn, In, Sn, and Bi as anodes for alkaline batteries, 235
Traction cells
lead–acid, real-time charge efficiency monitoring and on-charge gas evolution in tall, 155

Vanadium
primary 1.5 V Li cells with $BiVO_4$ cathodes, 29
small particle-size Li–V oxide; improved cathode material for high rate rechargeable Li batteries, 35
Voltage noise measurements
on sealed lead–acid batteries, 177

Zinc
development of new alloys of commercial Al (2S) with Zn, In, Sn, and Bi as anodes for alkaline batteries, 235
MnO_2–Zn cells, effect of amount of electrolyte in anode gel on rechargeability of alkaline, 145